












SUPER SLIM

- ▶ R410A On-off
- ▶ Concealed indoor unit for direct airflow
- ▶ Compact design (only 22.5cm height, 40-47cm depth)
- ▶ Horizontal or vertical mounting
- ▶ Up to 3m ducts
- ▶ Hydrophilic coated coils

-  Ceiling or Floor Mounting
-  Dual Control Operation
-  I Feel
-  Timer×4
-  Indoor Hydrophilic Coating
-  Sleep
-  Motion Detector (optional)
-  Autorestart
-  Auto
-  Wifi (optional)
- BMS**



▶ SUPER SLIM



▶ CONTROL PANEL

	Units	SUPER SLIM 25	SUPER SLIM 35
Cooling Capacity	kW	6.12	8.85
Heating Capacity	kW	6.28	9.35
Power Consumption	Cooling	1,800	2,630
	Heating	1,850	2,770
Efficiency	Cooling/Energy Label	3.30/A	3.37/A
	Heating/Energy Label	3.30/C	3.37/C
Dehumidification	LIT/H	3.4	3.6
Power Supply	Volt/Hz/Ph	230/50/1	230/50/3
Fuse Rating	A	16C	20/C
Cooling Range	C	15°~48°	15°~48°
Heating Range	C	-15°~ 24°	-15°~ 24°
Compressor Type		Scroll	Scroll
Piping Connections	Inch	1/4"-5/8"	3/8"-5/8"
INDOOR UNIT			
Dimensions (Width×Height×Depth)	mm	1200×400×225	1400×470×225
Air Flow/Turbo	m ³ /h	1,020/850/680	1,275/1,105/935
Sound Pressure Level at 1m at High Speed (power)	db(A)-pr	48(56)	48(56)
Sound Pressure Level at 1m at Medium Speed (power)	db(A)-pr	45(53)	45(53)
Sound Pressure Level at 1m at Low Speed (power)	db(A)-pr	42(50)	42(50)
Static Pressure (Max)	Pa	30	30
Weight	Kg	35	40
OUTDOOR UNIT			
Dimensions (Width×Height×Depth)	mm	900×640×440	900×860×440
Airflow	m ³ /h	2,300/1,500	2,300/1,500
Sound Pressure Level at 1m at High Speed (power)	db(A)	64(69)	64(69)
Sound Pressure Level at 1m at Low Speed (power)	db(A)	58(65)	58(65)
Weight	Kg	65	90